

Bestop Gray Trail Cover w/ Storage Sack

Installation Guide for Jeep Wrangler '07-'16 2-Door JK

Installation Time: <1 Hour

Tools Required:

- ✓ Box Cutter/Knife

Installation Instructions:

1. Carefully open the package using a box cutter or knife (Figure A) and ensure the trail cover is included and undamaged.



Figure A

2. Ensure that the vehicle is turned off before installing cover.
3. Begin by draping the trail cover over the top of the vehicle (Figure B). **Note:** The "Bestop" label should be on the passenger side if positioned correctly (Figure C).



Figure B



Figure C

4. Hook the adjustable straps to the underside of the vehicle on each side (two straps per side) (Figure D).



Figure D

5. With the straps hooked on both sides, cinch the straps down until the cover is snugly secured to the vehicle (Figure E).



Figure E

6. Locate the plastic strips (six on each side) toward the back end of the vehicle (Figure F).



Figure F

7. Slide the plastic strips into the belt rail retainer on each side of the vehicle (Figure G).



Figure G

8. Hook the adjustable straps on the rear of the trail cover to the bottom of the tailgate (Figure H).



Figure H

9. With the straps hooked, cinch the straps down until the cover is snugly secured along the rear of the vehicle (Figure I).



Figure I

10. **Optional:** *Locate the grommet on each side of the vehicle near the side mirrors. This can be used to install a cable lock securing the cover to the vehicle. To use this feature, thread a cable and lock through the grommet and through the mirror to secure.*



Before



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 10/10/2017