

Dirty Dog 4x4 Rear Netting - Black

Installation Guide for Jeep Wrangler '07-'16 2-Door JK

Installation Time: 1 Hour

Tools Required:

- ✓ Box Cutter/Knife
- ✓ Soft Top Tail Gate Clips (optional)

Installation Instructions:

1. Carefully open the package using a box cutter or knife (Figure A) and ensure all three pieces of the netting are included and undamaged.



Figure A

2. Locate the driver, center, and passenger sides (Figure B).



Figure B

3. Begin by attaching the first strap at the top of the bar behind the front driver's seat (Figure C).



Figure C

4. Attach the rear top strap at the top of the bar at the rear of the driver's side next (Figure D).



Figure D

5. Attach each lower strap going front to rear and keeping the spacing consistent (Figure E).



Figure E

6. Repeat Steps 3-6 on the passenger side (Figure F).



Figure F

7. Put the overhead piece on the vehicle and attach to the four straps at the top of both the driver and passenger sides already installed (Figure G).



Figure G

8. On the backside of the vehicle, attach the points into place using all eight buckles (four on each side) then adjust the tension so the net is centered (Figure H).



Figure H

9. Slide each half of the tail gate bar (included) into the lowest row (Figure I).



Figure I

10. Clip the full tail gate bar into the soft top clips (not included) (Figure J). **Note:** If not using a soft top (or soft top tail gate clips) this last row can be cut off).



Figure J

11. Secure the straps to the roll bar (Figure K). Ensure straps are run tight through the roll bar.



Figure K

12. Attach the straps at the top front corners over the speaker bar (Figure L).



Figure L

13. Adjust and tighten to center the entire netting.



Before



After