

**RedRock 4x4 Hitch Mounted Cargo Rack - 7 in. XL**  
**Installation Guide for Jeep Wrangler '07-'16 2-Door JK**

**Installation Time:** <1 Hour

**Tools Required:**

- ✓ Box Cutter/Knife
- ✓ ½" Socket
- ✓ Socket Wrench
- ✓ Hitch Pin

**Installation Instructions:**

**Note:** *This product requires a standard 2" receiving hitch in order to be installed.*

1. Carefully open the package using a box cutter or knife (Figure A) and ensure the cargo rack and hardware are included and undamaged.



Figure A

2. Place the cargo rack upside down on a flat surface (Figure B).



Figure B

3. Align the receiver bar with the two centered holes on the cargo rack (Figure C).



Figure C

4. Place the support brace over top of each centered hole (one on the bottom-front and one on the bottom-rear) (Figure D).



Figure D

5. Hand-tighten the supplied bolts (with a washer on each side) through the center of the support braces (Figure E), as well as the ends (Figure F).



Figure E





Figure F

6. Tighten each of the supplied bolts down using a  $\frac{1}{2}$ " socket (Figure G).



Figure G

7. Align the receiver bar with the 2" receiver on the vehicle and slide through until the hole of the receiver bar lines up with the hole of the 2" receiver on the vehicle (Figure H).



Figure H

8. Place a hitch pin through the hole to secure the cargo rack in place.



Before



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 11/07/2017