

Rugged Ridge Pocket Island Top - Khaki Diamond
Installation Guide for Jeep Wrangler '07-'18 4-Door JKU

Installation Time: 1.5 Hours

Tools Required:

- ✓ Box Cutter/Knife
- ✓ Hard Top Removal Tool/Torx Bit
- ✓ Windshield Channel

Installation Instructions:

1. Remove the two front freedom panels of the hard top (Figure A).



Figure A

2. Remove the rear hard top (Figure B).



Figure B

3. Layout the top in the sun to stretch the fabric from heat (Figure C).



Figure C

4. Connect the top to a windshield channel (not provided) (Figure D).



Figure D

5. Place the top over the vehicle (Figure E).



Figure E

6. Clip both inner straps to the center roll bar (Figure F).



Figure F

7. Run the fabric straps over the rear roll bar and through the buckle (Figure G).



Figure G

8. Attach the metal clips into the outer tub of the vehicle (Figure H).



Figure H

9. Run the rear strap around the rear bar (at the seatbelt) and connect into the oval hole of the rear tub (Figure I).



Figure I

10. Attach the Velcro straps around both roll bars (around handles if attached) (Figure J).



Figure J

11. Tighten the rear straps down (Figure K).



Figure K

12. Attach the windshield channel to the windshield bracket.

13. Tighten all straps down completely.



Before



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 07/13/2018