

Smittybilt G.E.A.R. Trail Shade

Installation Guide for Jeep Wrangler '07-'18 4-Door JKU

Installation Time: 1 Hour

Tools Required:

- ✓ Mallet/Hammer

Installation Instructions:

1. Remove all the contents from the carrier bag (Figure A).



Figure A

2. Locate the three male/female clasp on the shade and unclasp each (Figure B).



Figure B

3. Locate the buckle on each of the three straps removed from the shade in Step 2 (Figure C).



Figure C

4. Remove strap entirely from each buckle. Then, once completed, slide the strap through each of the top three rim holes of the spare tire (Figure D).



Figure D

5. With all three in place, tighten each down (Figure E).



Figure E

6. Reattach the shade by clipping each of the male/female clasps back in place (Figure F).



Figure F

7. Ensure all three have equal separation (Figure G).



Figure G

8. Locate the two poles and utilize the shock cords to assemble (Figures H & I).



Figure H



Figure I

9. Slide the thin end of each pole into the hole on each end of the shade (Figure J).



Figure J

10. Run the rope over the thin end of each pole (Figure K).



Figure K

11. Using a mallet or hammer, hammer the rope into the ground at an angle using the supplied stakes (Figure L).



Figure L



Before



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 09/25/2018