

Teraflex 2.5 in. Coil Springs-Rear Pair

Installation Guide for Jeep Wrangler '07-'18 4-Door JKU

Installation Time: 1 Hour

Tools Required:

- ✓ Jack
- ✓ Jack Stands
- ✓ 16mm Socket Wrench
- ✓ 18mm Socket Wrench

Installation Instructions:

1. Jack up the rear axle (Figure A).



Figure A

2. Place jack stands on both sides of the vehicle (Figure B).



Figure B

3. Remove both rear tires.
4. Remove both rear shocks using an 18mm socket wrench on the bottom and a 16mm socket wrench up top.
5. Lower the axle to release tension from the rear coil springs (Figure B).



Figure B

6. Press down lightly on the driver's side axle to unseat the coil spring (Figure C).



Figure C

7. Remove the coil spring from the driver's side (Figure D).



Figure D

8. Replace the driver's side coil spring with the new TeraFlex coil spring (Figure E).



Figure E

9. Repeat Steps 5-7 on the passenger's side.
10. Jack the axle back up to seat the coil springs properly (Figure F).



Figure F

11. Replace the rear shocks with 2.5" length shocks or shock extensions.

12. Reinstall rear tires and remove the jack stands.



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 11/11/2018