

## Tuffy Compact Security Lockbox

### Installation Guide for Jeep Wrangler '07-'16 2-Door JK

**Installation Time:** 1 Hour

**Tools Required:**

- ✓ Box Cutter/Knife
- ✓ Drill
- ✓ Drill Bit
- ✓ 13mm Wrench
- ✓ Marker

**Installation Instructions:**

1. Carefully open the package using a box cutter or knife (Figure A) and ensure the hardware is included and undamaged.



Figure A

2. Open the lockbox (Figure B).



Figure B

3. Line the opening with the sealant (provided) (Figure C).



Figure C

4. Ensure the lockbox will close and lock still (Figure D).



Figure D

5. Place the lockbox where it will be mounted (and remove carpeting if placed in interior) and mark each of the four holes with a marker (Figure E).



Figure E

6. Drill each of the four holes marked in Step 5 (Figure F).



Figure F

7. Insert each of the four bolts (supplied) through the drilled holes (this method is more secure than placing the bolt through the lockbox) (Figure G).



Figure G

8. Align the lockbox with the four screws so they are protruding through the interior of the lockbox (Figure H).



Figure H

9. Place a washer (provided) and locknut (provided) on each of the four bolts then tighten using a 13mm wrench (Figure I).



Figure I



Before



After

Installation Instructions Written by ExtremeTerrain Customer J. Sandlin 06/04/2018.