REDROCK

SIDE STEPS

(2007-2018 Wrangler JK)

INSTALLATION INSTRUCTIONS

CONTENTS

- (2) Side Steps
- (4) Brackets + (2) 4dr
- (4) Nut Plates + (2) 4dr
- (8) Small Washers + (16) 4dr
- (4) Large Washers + (2) 4dr
- (4) Extra Large Washers + (2) 4dr
- (8) Hex Head Bolts + (4) 4dr
- (8) Small Bolts + (4) 4dr
- (4) Medium Bolts + (2) 4dr
- (4) Large Bolts + (2) 4dr
- (12) Small Lock Washers + (6) 4dr
- (4) Large Lock Washers + (2) 4dr
- (8) Nuts +(4) 4dr

TOOLS REQUIRED

13mm,16mm Socket Ratchet 10mm Wrench 4mm Allen Key





Insert a nut plate for each bracket into the existing holes on the bottom of the body.



STEP 2

Place the correctly labeled bracket behind the pinch weld and loosely secure both holes with a hex head bolt with a washer placed through the pinch weld and bracket, then hand tightened with a washer and nut on the inside.





STEP 3

Insert a large bolt, with a washer through the bracket and into the body hole that contains the nut plate. Hand tighten the hardware.



STEP 4

Find the left and right steps; install 2 bolts, with lock washers and washer, through the brackets into the threaded bottoms of the side steps. Tighten down hardware on the body then secure the steps in place.