Installation Instructions for Barricade Matte Black Grille Cover (07-14 Wrangler JK) Item # J100721

Tools RequiredGrille Cover (J100721)
Small Flathead Screw Driver Old Credit Card or Floss Adhesive Remover Knife

Before...



Installation Instructions Removing the Jeep Icon

Step 1:Using an old credit card (or floss which can work equally as well...), slide the card behind one of the letters as shown below to pry the letters off.



Step 2: Using an adhesive remover, wipe remaining glue off the grill. After cleaning, the surface should be clean of adhesive as shown in the picture on the right below.

Before... After...





Installing the Barricade Grille Cover

Step 1: Using a small flat head screw driver, remove the 2 plastic tabs from the top of the factory grill by prying the tabs upwards. There is one on each side above the head lights.





Step 2: Pull out the two tabs from step 2. Save these for later installation. The picture below shows the tabs removed.



Step 3: Completely clean the stock grill cover. Remove any dust, dirt, bugs, etc. Once clean, use the included alcohol wipes to clean the grill one last time before adhesion.

Step 4: Remove the red adhesive covering off of the tape on the back of the grille cover. This will leave the white tape exposed. The exposed tape is shown below.



Step 5: GENTLY press the grille cover onto the grill. DO NOT completely seat the cover onto the grill at this point.

Step 6: As you can see in the picture below, the holes for the plastic tabs do not completely line up at this point. This is OK.



Step 7: Check the fitment around the weather rubber strip on the top of the grill. In the picture below the weather strip is the correct size, as the cover fits cleanly next to the weather strip.



Step 8: If needed, trim the weather strip using a knife. In the picture below on the left, the passenger side strip below is too long and needs trimmed to fit the cover as shown on the right.





Step 9: Once complete, firmly press the grill cover onto the grill.

Step 10: Reinstall the plastic push tabs removed in step 2. First push the tab into the hole as shown in the picture below on the left. Then press the center portion down firmly until seated as shown below on the right.





Step 11: Enjoy your grill cover!!!



Installation Guide Created by ExtremeTerrain Customer Mike Marcantonio on 10.27.15