



ONE PIECE WRAPAROUND NET

YJ/ TJ WRANGLER '92-'06

1. Lay the net out on a flat surface with the label facing up and at the right side.
2. The label will face out on the right side of the Jeep when installed.
3. Loosely connect the upper most webbing with connector around the roll bar on the passenger side just above the seat belt bolt.
4. Do the same with upper most strap on the drivers side.
5. Connect the balance of the straps.
6. Adjust as necessary for proper alignment of the vertical and horizontal straps.
7. Conceal the strap ends by pushing them back through the plastic connectors and rolling them up.

Note: Steel roll bar cages are subject to expansion and contraction with temperature variations. Occasional tightening of the net may be needed at first and best done in the morning when cool.

Tip: To pull straps extra tight, grip with a pair of pliers when tightening.



BARRICADE

OFF - ROAD ARMOR

TJ/YJ REAR OVERHEAD NET '92-'06 JEEP WRANGLER

Lay the net out on a flat surface with the label at the top right. When the net is installed, the label will be facing up on the right hand side of the Jeep.

Attach the straps around the roll bar and back to the plastic connectors (see photo). Adjust as needed.

To conceal the strap ends, feed them back through the slot in the plastic connector and roll up.

When used in combination with the One Piece Wraparound Net, the two nets can be attached with the hook & loop fasteners provided.

Note: Roll bar cages and webbing are subject to expansion and contraction with temperature variations. Occasional tightening may be necessary and best done in the morning when cool.

Tip: Use pliers to grip the strap end to pull extra tight.

