



FIRE EXTINGUISHER & ACCESSORIES MOUNT BRACKET INSTALLATION INSTRUCTIONS

FITS: 2007-13 JEEP JK PART NO: JP-181110-A

Thank you for purchasing a quality Drake Off Road product. Please refer to the installation instructions below when installing this product.

TOOLS REQUIRED:

- 18mm socket and ratchet
- #3 Phillips Screw Drive

INSTALLATION:

- Step 1:** Remove two bolts securing front seat bracket to floor.
- Step 2:** Attach fire extinguisher or accessory mount to bracket using supplied hardware (2 bolts, 2 nuts). Make sure bracket is attached so that pull knob is facing upwards when installed.
- Step 3:** Place supplied spacer over bolt hole closest to door.
- Step 4:** Install bracket using factory removed hardware. Torque bolts to 45ft lbs.
- Step 5:** Attach other half of fire extinguisher or accessory mount to bracket and secure fire extinguisher in desired location and orientation.

Note: Fire Extinguisher Mount (FIREX-MNT-DOR) or Accessory Mount (LIGHT-MNT-DOR) not included.


SATISFACTION GUARANTEE:

If you are not happy with this product, for any reason, or found product to be defective in manufacturing, simply return it to Drake Off Road within 30 days of purchase and we will replace it - no questions asked. We stand behind our products one hundred percent, so you can sit behind the wheel with pride.


**Proof of purchase and dated receipt must be present with any return. All returned products are tested and if found to be damaged by the installer, no replacement will be issued. You pay the the cost to ship to us, we pay for the return shipping. Guarantee does not include any labor and/or tax charges incurred.*



Step 1



Step 2



Step 3 & 4



Step 5



Questions about Drake Off Road products, visit www.DrakeOffRoad.com or call our customer service department toll free:

855.DRAKEOR
702.853.2060



Mon - Thurs 7:45 a.m. to 5:00 p.m. PST
Friday 7:45 a.m. to 4:30 p.m. PST

IS-DOR-JP-181110-A