




DELTA



MADE IN USA






DELTA JEEP® GRILL LIGHT BAR For JEEP Wrangler 2007-2012

P/N 01-9530-3BX

I. INSTALLATION INSTRUCTION for JK Model 2007-2012

1. Remove the plastic cover between the grill and the front bumper and thread both holes in the frame with a 1/2" screw-tap for #20-thread size (not included).
2. Attach both arms to the frame using (2) bolts (provided).
3. Attach cross-bar to driver's side arm using (2) small hex bolts. (provided)
4. Attach cross-bar to passenger's side arm using (2) small hex bolts (provided).
5. Route the harness under the grill and into the engine compartment towards the battery location.
6. Install the relay in a close proximity to the battery.
7. Connect black wire leading from relay to metal surface under the hood with a sheet metal screw (provided).
8. Route the blue (switch wire) alongside the firewall to the driver's side and puncture through the rubber grommet (per photo) to get inside the passenger compartment.
9. Install the switch on the dashboard (left to the steering column) by snapping the side panel of the dashboard and drilling 1/2" hole in the dashboard. For best result use our Billet Aluminum Switch Plate #05-2001-3X
10. Connect blue wire to the switch prong with lamp icon.
11. Connect the short red wire from the prong with + icon on the switch to any "hot wire" using snap-lock (provided).
12. Connect the black wire leading from the switch to any grounded metal surface under the dash-board.
13. Remove the fuse from the harness and connect the red wire leading from the relay to the positive post on the battery.
Now insert the fuse back into the fuse holder.

You may now test your lights! **HAPPY FOUR WHEELIN'**



DELTA TECH INDUSTRIES, LLC - ONTARIO, CA 91761, U.S.A.

Web: www.deltalights.com E-mail: tech@deltalights.com

Rev. 4/12