Rhino Rack Installation Guide

Installation Time: 10-15 Minutes

Tools Required:

- ✓ 4 mm Allen key
- ✓ Box cutter
- ✓ Rubber mallet
- ✓ Phillips screw driver
- ✓ Tape measure

Installation Instructions:

- 1. Open all contents and lay them out
- 2. Snap the rubber protectors into the rail starting from one end
- 3. Piece number three will need to be trimmed down to size. (cut flush with the rail)
- 4. Use the mallet to tap the end caps into place
- 5. Use the Philips screw driver to place the screw into place to hold the end cap on.
- 6. Place the metal spacer and the plastic end cap cover to each end
- 7. Place the locking washer and the spacer washer onto the long screws and feed them in through the holes to get them to hold the spacer and end cap cover in place. (do not tighten)
- 8. Place the little rubber sleeve onto the bottom of the end cap
- 9. Place the one of the racks onto your jeep roof
- 10. Make sure you the spacer and end cap go over the roof rail
- 11. Tighten one side of the rail and measure the distance of the rack from the end of the rail
- 12. Go to the other side of your jeep and measure the distance of the rack and make sure both sides match before tightening
- 13. Repeat steps 8-12 for second rack
- 14. Enjoy your new rhino rack

Installation Instructions Written by ExtremeTerrain Customer Christopher Timonian 01/25/2016













