

Installation Guide for Bestop All Weather Trail Cover w/ Stuff Sack (97-06 Wrangler TJ)

Installation Time: 15 minutes.

Tools Required:

✓ None

Pre-Installation notes:

In this install guide, we are installing the Bestop All Weather Trail Cover w/ Stuff Sack (97-06 Wrangler TJ) in Charcoal color. This trail cover is also available in Spice color.



Un-boxing and Parts List:

The package contents consist of the trail cover neatly folded in the stuff sack and the instructions.



Installation Instructions:

1. First, remove the trail cover from the stuff sack and lay it out on the ground to determine its orientation. It is much easier to put the cover on the Jeep with the correct orientation than try to rotate it after it is on top of the Jeep. An easy way to determine orientation is the brass rings (for securing cover with a cable lock) are on the sides towards the front of the Jeep near the rear-view mirrors.



2. Once cover is laid out and orientation is determined, lay the cover across the top of the roll bars.



3. Pull the cover over the cab area and ensure that it is overall even and situated correctly.

Notice: When installing the trail cover the first few times, the fit can be quite tight. Installing the cover in warmer weather helps as the canvas material will be easier to stretch.

4. Notice the strips that go into the rear side channels, similar to some soft tops. It is best to secure these first. Start with the front of the strips and get it started and then work your way towards the back. The Jeep may or may not have the tailgate brackets used for soft tops. If the Jeep does not, you will not be able to affix the strips at the rear.



5. Loop the tail light straps over the tail lights.



6. Loop the spare tire strap under the spare tire. You might want to tie part of the end off in order to make the fit more snug (optional).



7. Pull the windshield cover tight and loop the windshield straps over the windshield hinges or lights if equipped.



8. Secure the rocker panel strap hooks underneath the bottom of the rocker panels and tighten the straps. There are two straps on each side of the Jeep.



9. Once complete check that the trail cover is pulled tight and secure all around. The cabin of the Jeep should now be protected from the elements. Optional cable lock rings are available for use for additional security. Refer to the owner's manual for information on how to use them.

