

# Spare Tire Relocation Bracket

## Installation Instructions

**PART NUMBER: J130909**  
**FITS Jeep Wrangler JK**  
**07-18**

<u>KEY TO COMPONENTS</u>	<u>TOOLS NEEDED</u>
A. 1 ea. Relocation bracket B. 3 ea. ½-20 Flange nut	Socket drive 19mm Wrench 18mm wrench 21mm socket

A



B



Please take a few minutes to read and thoroughly familiarize yourself with the installation procedures outlined in this manual. Following the steps as outlined will save you time and help reduce mistakes. Once the instructions are reviewed, if you feel that you are not capable of safely installing the parts seek the help of a qualified installation expert to help you complete the job. The manufacture is in no way responsible for any personal injury or vehicle damage that may occur during the installation.

### California Proposition 65 Warning!

This product may contain one or more chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## FACTORY TIRE REMOVAL

### Step 1

- Remove spare tire from OE tire carrier. Set hardware aside for later use.



## INSTALLING TIRE RELOCATION BRACKET

### Step 1.

- Place supplied tire carrier onto the factory tire carrier fig 3. (image shown as reference)
- Secure relocation bracket onto the vehicle by installing all three supplied flange nuts (B). Tighten down using a 18mm wrench.
- Reinstall spare tire onto the relocation bracket. Secure spare tire into position by installing factory lug nuts. Tighten down using a 21 mm socket.
- This completes the installation.

Fig 1

