



Installation Instructions

Combo Top, 07- Wrangler 2 door and Unlimited 4 door

Part numbers covered by these instructions: 948xx, 949xx

PLEASE NOTE: This combo top requires the use of the Rampage 901007 Windshield Channel for installation.

IMPORTANT NOTICE:

Carefully read the instructions before attempting to install this product. Rampage Products is in no way responsible for any damage to the vehicle or personal injury that may occur during the installation or use of this product.

INCLUDED COMPONENTS

- 1 - 2 piece Combo Top with Pre Installed straps
- 1 - Rear Portion Storage Bag

NOTE Unfold the Combo Top (except mesh version) and lay it in direct sunlight for at least 30 minutes. For best results the temperature should be over 70 degrees. If it is not you can still install the Combo Top but you will need to tighten the straps after use until it stretches smooth.

Installation

1. Remove any hard or soft top currently on your Jeep. **Also remove the door surrounds for ease of installation.**
2. Install the Combo top onto the header channel using the snaps as shown in the illustration. (fig 1)
3. Place the header channel with the top installed above the windshield on the gasket and fold the combo top forward over the windshield.
4. Insert the tab of the header channel into the footman loop on the vehicles windshield frame as shown. (Fig. 2)

Fig 1




Fig 2



5. Place the metal bracket in place on under the header channel as shown. (fig 3).
6. Insert the threaded knob into the metal bracket and tighten. (fig 4) Repeat for other side.

Fig 3



Fig 4



7. Wrap the front side flaps under and around the sides of the roll bar (above the front seats) and back onto themselves and secure with the velcro strips. Fig 5, fig 6.

Fig 5




Fig 6



8. Now wrap the roll bar straps around the center roll bar as shown (fig 7). Locate the long straps with the plastic clips on the ends. These wrap under the roll bar and are inserted into the holes on the sound bar at "A" in figure 6. They should be pushed in until the catch inside the hole.
9. Now wrap the straps and flap around the sound bar in the center of the top (fig 7 "B") and tighten.

Fig 7



10. Hook the rear side rail straps to the belt rail of the vehicle on the sides as shown at "C" Fig 8.
11. Wrap the rear corner straps ("D" Fig 8) around the rear seat belt mounting points and tighten.
12. On 4 door vehicles only fasten the two straps around the rear of the roll bar.

Note: on the 2 door the strap goes around the sides and stretches across the rear roll bar. It is important to be sure this is very tight to eliminate flapping at high speeds.

Fig 8



13. Wrap the mid flap around the side of the roll bar as required. ("E")
14. At the front of the top just behind the windshield there is a thin velcro strap on each side. Wrap this around the front of the roll bar to keep the front section secured properly.
15. Be sure to repeat all operations for both sides.



NOTE: The top will work with the door surrounds installed or not with either soft upper doors or full doors. It is not intended to be watertight - do not use in place of a full top in wet weather conditions.

Important Care Instructions:

Convertible tops and accessories require special care if you want to get the maximum usage and enjoyment from them. The following recommendations, if followed carefully, can extend the life of your top or accessory.

Hand wash using a mild non-detergent soap such as ivory. Use a non-abrasive cloth or sponge. Rinse thoroughly.

Do not wash in direct sunlight and avoid automatic car washes

When your top is clean, we recommend using "Ragg Topp" or "303 Protectant" on both the vinyl top and windows. This product contains a sunscreen that helps protect from the sun's damaging rays. Stay away from products containing alcohol, as it will cause the fabric and windows to lose their elasticity, thus reducing the life of your top or accessory. If you are unable to locate "RaggTopp" Please call 1-800-377-4700 for a distributor near you. For "303 Protectant", please call 1-800-223-4303 for a distributor near you.

Direct sunlight and heat are the biggest enemies of the windows. Park in the shade whenever possible. If you must park in the sunlight, rotate the direction that you park every few days so all windows get even exposure.

Our tops are designed so that you may roll up and/or store the rear curtain and side curtains. To prevent scratching of the windows, be sure that windows are completely clean and free of dust particles. Even a little dirt will badly scratch the windows. You may want to use a soft cloth when rolling up or storing your windows. Heat may build up on rolled up windows, so be sure to unroll them frequently. If you roll up the windows at the beginning of summer and leave them, they may be ruined by fall.

Do not open or roll up windows at temperatures below 45 degrees F this could cause them to crack or break.

Zipper Care.

DO NOT use pliers or other tools to pull on zippers. If the zipper requires more force than pulling with your fingers something is most likely out of alignment or improperly installed. Be sure the top is up to a temperature of 70 deg., and that the components are installed correctly and in the correct sequence to ensure protection of the zipper.

Zippers require periodic cleaning and lubrication to ensure longevity and ease of use. Clean by wiping with a towel soaked in soap and water, DO NOT USE HARSH CHEMICALS. Zipper lubricants are available at sporting goods stores and online for wetsuits. An occasional use will keep the zipper slides operating as new.

Warranty Information

Rampage products, Inc. warrants to the original purchaser of any top it manufactures, that the top will be free of defects in material or workmanship for a period of 1 year from date of purchase. Such obligations under this warranty shall be limited to the repair or replacement, at Rampage products discretion, of any assembly or parts which, upon examination by Rampage products, Inc. proves to be defective. All defective items must be returned with proof of purchase to Rampage products, Inc., freight prepaid. This warranty does not cover damage resulting from abuse, misuse, alteration, accident or damage in transit. Rampage products obligations under this warranty are limited to the aforementioned repair or replacement of warranty defects for which the return authorization has been received during the warranty period, and Rampage products, Inc. shall not be liable for any incidental or consequential damages arising from breach of this or any implied warranty.

Rampage Products, Corona, CA Phone: (951) 277-4949 Fax: (951) 277-2295

www.rampageproducts.com

Made in China