

INSTALLATION INSTRUCTIONS

Drawer Riser Kit part #072

Please read and fill out the enclosed warranty registration card to activate your warranty.

Shipping Package

- (4) 5/16 X 2 ¼" bolts
- (8) 5/16" Washers
- (4) 5/16" NyLock Nuts
- (4) 1" Spacer

Mounting Directions

- 1. Follow the mounting instructions included with the drawer but replace the drilling and fastening portion of the instructions with these steps.
- 2. Place the drawer in the vehicle and mark the (4) drilling locations on the floor using the (4) holes in the bottom of the drawer as a marking template. Make sure the drawer will open and close when it is elevated 1" before marking.

<u>Warning:</u> Make sure there is nothing under the vehicle that will be damaged during drilling. The gas tank is usually located in the rear of the vehicle.

- 3. Cut the carpet if necessary and drill out the (4) marked spots on the floor corresponding with the holes in the bottom of the drawer.
- 4. Fasten down the drawer with the (4) 5/16 x 2 ¼" bolts, (4) 5/16 nuts, and (8) 5/16 washers using (4) 1" spacers between with bottom of the drawer and the floor of the vehicle to raise the drawer up.
- 5. Continue following the remaining installation instructions that came with the drawer.

Call (970) 564-1762 for Technical Support